

Conference System ADN

ADN is an excellent product for conference rooms of hotels and all types of meeting venues.

Attendees in conference meetings need to concentrate on the discussions at hand, and that's why they prefer to work with a system which is easy to operate.

Conference organizers also prefer working with a system that is flexible and easy to setup for various types of meetings with variable numbers of delegates. ADN is the ideal system which meets your requirements. It is full digital and takes advantage of the latest technology and standards in professional conference management systems. Its flexibility makes ADN is an ideal investment for your organization. ADN can be ordered with various configurations and features which meet the needs of your conference applications from small meetings all the way to large conferences.

- USB port for recording the sound of the meetings on storage media
- Standard network cables makes maintenance of the system easier in future
- A pair of speakers in each of the Delegate or Chairman units
- Auto tracking up to six cameras from the Main Unit
- Hot swapping of the Delegate units during operation
- Can choose which camera output to be send to the video output of the system
- Four video outputs with no need to use a distributor
- Can be used jointly with Simultaneous Translation System
- Main Unit Supports up to 120 Delegate units
- Supports large installations of up to 1200 Delegate units with more Main Units
- Headphone interface with adjustable audio volume
- Audio output for external speakers in the room
- Two XLR and RCA audio outputs
- Two XLR and RCA audio inputs
- Enhanced echo suppression technique
- Feedback and surrounding noise suppression



Input Voltage	220-240 V
Output Voltage	24 V
Weight	4.6 Kg
Power	200W
Dimension	417x100x350 mm

Chairman

ADN C1

Delegate

ADN D1



Headphone output connector	3.5 mm , 16Ω
Microphone frequency response	30 - 20000 Hz
Signal to noise	103 dB
Microphone sensitivity	-47 dB
Power	3.5 W
Voltage	24 V
Current output	45 mA
Total harmonic distortion (THD)	< 0.05%



Auto tracking
up to six cameras
from the Main Unit

