

# Conference System

BK 780

BK 780 is an excellent product for conference rooms of hotels and all types of meeting venues.

Attendees in conference meetings need to concentrate on the discussions at hand, and that's why they prefer to work with a system which is easy to operate. Conference organizers also prefer working with a system that is flexible and easy to setup for various types of meetings with variable numbers of delegates.

BK 780 is the ideal system which meets your requirements. It is full digital and takes advantage of the latest technology and standards in professional conference management systems. Its flexibility makes BK 780 an ideal investment for your organization.

BK 780 can be ordered with various configurations and features which meet the needs of your conference applications from small meetings all the way to large conferences.

- 350 W Power supply which supports up to 60 delegate units
- Up to 240 delegate units with auxiliary power supply
- 4 output ports for delegate Mics
- Adjustable sound volume for balanced and unbalanced audio output
- Adjustable sound volume for Aux audio input
- Adjustable sound volume for Headphone output while monitoring conference audio
- Automatic shut down of the system
- Display screen for system configuration
- Multiple conference management modes such as limit on active Mics, taking turn to speak and open discussion mode
- Camera output for camera tracking system



Frequency Response	50-16000 Hz
Signal-To-Noise	90 dB
Distortion	< 0.2% 1KHz
Output Impedance	600 Ω
Power	350W



BK 900-D

## Delegate

## Chairman

BK 900-C



- Frequency response: 50 to 16,000 Hz
- Sensitivity: 42 dB
- On/Off switch and status display indicator
- Circular lamp around the neck of the microphone to indicate its On/Off status
- Input Voltage: 24 V DC
- Two audio output connectors to be used for headphones or audio recorders

- Frequency response: 50 to 16,000 Hz
- Sensitivity: 42 dB
- On/Off switch and status display indicator
- Circular lamp around the neck of the microphone to indicate its On/Off status
- Input Voltage: 24 V DC
- Two audio output connectors to be used for headphones or audio recorders

- This microphone has the following features in addition to all the features of the Delegate Unit microphone:
- Control button for priority of speakers and silencing all the Delegate Unit microphones
  - No constraints in positioning of the Chairman Unit with respect to the chain of the Delegate Unit microphones.