

Wireless Microphone

BW 112

With its state of the art technology in wireless audio systems, BW 112 possesses unique features such as easy setup, user friendliness and reliability. BW 112 wireless microphone system is comprised of a receiver, a portable transmitter, a lavalier ME2 microphone plus accessories.

BW 112 consists of a True Diversity receiver with two antennas which receives signals simultaneously and processes the strongest one. This product is perfect for all kinds of applications in studios, convention halls and meeting rooms.

An infrared wireless connection between the portable transmitter and the receiver synchronizes the two devices.

The backlit display on both the transmitter and the receiver facilitates reading the information in locations with low lighting.

- EM100
- SK100
- ME2

| | |
|-----------------------|-------------|
| Frequency range | 780-822 MHz |
| Noise reduction | HDX |
| Frequency response | 25-18000 Hz |
| Signal to Noise ratio | > 110 dB |
| Distortion | < 0.09% |

| | |
|-------------------------|-------------------------|
| EM | |
| Antenna | 2x BNC, 50 Ω |
| Balanced audio output | XLR, +18 dB u |
| Unbalanced audio output | 1/4" connector, +12 dBu |
| Dimensions | 202x212x43 mm |
| Weight | 900 g |

ME 2

| | |
|--------------------------------|-----------------|
| Capsule | Condenser |
| Sensitivity | 20 mV/Pa |
| Pattern | Omnidirectional |
| Maximum Sound Pressure (SPL) | 130 dB |
| Frequency response | 30 - 20000 Hz |

SK

| | |
|------------------|------------------------|
| Output power | 30 mW |
| Power | 2x AA battery standard |
| Operating time | About 8 hours |
| Microphone input | 1.8 Veff |
| Line input | 3 Veff |
| Dimensions | 82x64x24 mm |
| Weight | 200 g |

