

Wireless Microphone

BW 112 P meets your requirements for flexible and professional wireless communication with an easy setup and reliable operation.

BW 112 P wireless microphone system is comprised of a portable receiver, a portable transmitter, a lavalier ME2 microphone plus accessories.

This product is perfect for all kinds of applications in studios, convention halls and meeting rooms and in locations where it is required for the receiver to be portable.

An infrared wireless connection between the transmitter and the receiver synchronizes the two devices. The backlit display on both the transmitter and the receiver facilitates reading the information in locations with low lighting.

Frequency range	780 - 822 MHz
Noise reduction	HDX
Frequency response	25-18000 Hz
Signal to Noise ratio	> 110 dB
Distortion	< 0.09%

EK 100

Power	2x AA battery
Operating time	6-10 hours
Audio output	3.5 mm
Signal to noise ratio	> 110 dB
Sensitivity	< 2.5 µV
Dimensions	82x64x24 mm
Weight	200 g

BW 112 P

- 🔊 EK100
- 🔊 SK100
- 🎤 ME2



ME 2

Capsule	Condenser
Sensitivity	20 mV/pa
Pattern	Omnidirectional
Maximum Sound Pressure (SPL)	130 dB
Frequency response	30 - 20000 Hz

SK

Output power	30 mW
Power	2x AA battery standard
Operating time	About 8 hours
Microphone input	1.8 Veff
Line input	3 Veff
Dimensions	82x64x24 mm
Weight	200 g