

Wireless Microphone

With its state of the art technology in wireless audio systems, BW 122 possesses unique features such as easy setup, user friendliness and reliability. BW 122 wireless microphone system is comprised of a receiver a portable transmitter, a lavalier ME 4 microphone plus accessories.

BW 122 consists of a True Diversity receiver with two antennas which receives signals simultaneously and processes the strongest one.

The Cardioid microphone prevents unwanted feedback from the environment.

A wireless infrared connection between the portable transmitter and the receiver synchronizes the two devices. The backlit display on both the transmitter and the receiver facilitates reading the information in locations with low lighting.

The features of this product makes it perfect for all kinds of applications in studios convention halls and meeting rooms.

BW 122

- EM 100
- SK 100
- ME 4

Frequency range	780 - 822 MHz
Noise reduction	HDX
Frequency response	25-18000 Hz
Signal to Noise ratio	> 110 dB
Distortion	< 0.09%

EM 100

Antenna	2x BNC, 50 Ω
Balanced audio output	XLR, +18 dB u
Unbalanced audio output	1/4" connector, +12 dBu
Dimensions	202x212x43 mm
Weigh	900 g

ME 4

Frequency response	50 - 18000 Hz
Capsule	Condenser
Pattern	Cardioid
Connector	3.5 mm
Sensitivity	40 mV/Pa
Noise level	31 dB
Sound Pressure level (SPL)	120 dB



SK 100

Output power	30 mW
Power	2x AA battery standard
Operating time	About 8 hours
Microphone input	1.8 Veff
Line input	3 Veff
Dimensions	82x64x24 mm
Weight	200 g

