




BW 122 P

-  EK 100
-  SK 100
-  ME 4

Wireless Microphone

BW 122 P is a state of the art product in wireless audio technology which is flexible, user friendly and reliable. It consists of a portable receiver, a portable transmitter, a lavalier ME 4 microphone plus accessories.

The cardioid microphone rejects the off-axis sound and reduces feedback. A wireless infrared connection between the portable transmitter and the receiver synchronizes the two devices. The backlit display on both the transmitter and the receiver facilitates reading the information in locations with low lighting.

This product is perfect for all kinds of applications in studios, convention halls and meeting rooms and in locations where it is required for the receiver to be portable.

Frequency range	780 - 822 MHz
Noise reduction	HDX
Frequency response	25-18000 Hz
Signal to Noise ratio	> 110 dB
Distortion	< 0.09%



EK 100

Power	2x AA battery
Operating time	6-10 hours
Audio output	3.5 mm
Signal to noise ratio	> 110 dB
Sensitivity	< 2.5 µV
Dimensions	82x64x24 mm
Weight	200 g



ME 4

Frequency response	50 - 18000 Hz
Capsule	Condenser
Pattern	Cardioid
Connector	3.5 mm
Sensitivity	40 mV/Pa
Noise level	31 dB
Sound Pressure level (SPL)	120 dB



SK 100

Output power	30 mW
Power	2x AA battery standard
Operating time	About 8 hours
Microphone input	1.8 Veff
Line input	3 Veff
Dimensions	82x64x24 mm
Weight	200 g