

Wireless Microphone

With its state of the art technology, BW-112P wireless microphone system is easy to operate; is set up quickly and is highly reliable.

BW-112P includes a portable transmitter and receiver plus an ME2 lapel microphone and accessories. The features of the product make it ideal for use in studios, conference venues and meeting rooms.

BW 112 P

- 🔊 TB101
- 📡 RB101
- 🎤 BE-50



BE 50	
Element	Back Electret Condenser
Polar Pattern	Omn-directional
Frequency Response	20HZ-20KHZ
Sensivity	-45dB±3dB
Output Impedance	2K Ω±30%
SPL max	140dB
Cable	Φ1.4x1.2m
Accessory	Tie-clip,wind screen

TB101	
Carrier Wave Frequency Band	UHF 500-980 MHZ
Modulation System	FM
Output Power	5mW-10mW
Frequency Bandwith	12-24 MHZ
Harmonic Radiation	<-60 dB
S/N Ratio	>97 dB
T.H.D	1%@1KHZ
Frequency Response	50HZ-15KHZ



RB101	
Carrier Wave Frequency Band	UHF 500-980 MHZ
Modulation System	FM
Effective Operating Range	60m (open place)
Frequency Bandwith	12-24 MHZ
Output Socket	3.5mm
S/N Ratio	>97 dB
T.H.D	1%@1KHZ
Frequency Response	50HZ-15KHZ